

E eTERMINAL S22+


Self-Service Kiosk

With its ultra-compact chassis, you may fits S22+ place in every shop concept. The dual sided kiosk is optimized for a high workload capacity, ensures less queues for customers during peak times.

Highlights



Dual-sided kiosks, standing & wall mount options



21.5" FHD industrial-grade LCD with PCAP touch panel



High add on modularity with printer, camera, proximity sensor



Optional status indicator, scanner, MSR, FRID/NFC reader



Minimum space requirement



Super sleek design



Specifications

CPU Support	Intel Core I3	Intel Core I5	RK3568 (2.0GHz)
System Memory	1x DDR3L/DDR4, SO-DIMM, 4GB (Max. 16GB)		DDR4,4G (Onboard)
Storage Device	1x mSATA / M.2 128G (64G/256G optional)		eMMC 32G
Power	1x 12V-5A/60W+1 x 24V-2A/48W		
OS Support	Win 10		Android 11.0

LDC

Size	21.5" TFT LCD Panel
Brightness	1920*1080
Resolution	250 cd/m ²
Touch Screen	True-flat Projected Capacitive Touch

EXTERNAL I/O PORT

DC-IN	1x DC In	
CR	N/A	1xRJ11
VGA	1x VGA	N/A
HDMI	1x HDMI	N/A
USB	2x USB 3.0 +6 x USB 2.0 Ports	
LAN	1x LAN (10/100/1000Mb)	
Audio	1x MIC-IN & 1x LINE-OUT	N/A
Serial Port	1x DB9 (RS-232)	1x RJ12 (RS-232)

STANDARD COMPONENTS

Printer	80mm thermal printer, auto cutter, 170mm/sec (max.)
Camera	5MP Single Camera
Proximity Sensor	60-80cm Proximity Sensor
Speaker	2 x 2w Speaker

OPTIONAL

WIFI	mPCI-E WiFi/BT module	WiFi/BT(onboard)
Scanner	1D, 2D Scanner	
MSR	Yes	
NFC/RFID Reader	Yes	
Status Light	Printer status light (Red light indicates error or out of thermal paper, Blue light indicates working status)	
System FAN	4x Fans (Manufacturer default)	

ENVIRONMENT

Operating Temperature	0 °C - 50 °C
Storage Temperature	20%RH - 90%RH
Operating Humidity	-20 °C - 70 °C
Storage Humidity	10%RH - 90%RH

PHYSICAL DIMENSION

Principal Machine	814*410*101.4mm
Column	1209*120*80mm
Chassis	500*480*6mm

CUSTOMIZED

Circuit Breaker	2P Circuit Breaker + Power Extension Socket
-----------------	---

